

WEST LAFAYETTE FIRE DEPARTMENT

300 NORTH ST• WEST LAFAYETTE, INDIANA 47906

MAIN PHONE: 765-775-5175

Commercial Inspection Checklist Pre-plans

FIRE HYDRANTS	Р	F	N/A
 CONSISTENT WITH PLAN REVIEW 	[]	[]	[]
PRIVATE OR PUBLIC	[]	[]	[]
 OBSTRUCTED/ACCESSIBLE (4' clearance) 	[]	[]	[]
 PROPER CONNECTIONS (two steamers 5") 	[]	[]	[]
VEHICLE IMPACT PROTECTION	[]	[]	[]
 SIZE OF WATER MAIN FEEDING HYDRANT 	[]	[]	[]
 PROPER DIRECTION (Steamer faces toward fire lane) 	[]	[]	[]
FIRE DEPARTMENT CONNECTION	Р	F	N/A
ACCESSIBLE / FIRE LANE	[]	[]	[]
 HEIGHT REQUIREMENT (30-40" from grade) 	[]	[]	[]
 PROPER CONNECTION (5" STORZ, or 2-21/2 &5" STORZ") 	[]	[]	[]
 FDC PAINTED RED (Out of the Vault) 	[]	[]	[]
FDC IDENTIFICATION SIGN	[]	[]	[]
VEHICLE IMPACT PROTECTION	[]	[]	[]
FIRE SERVICE VAULT	Р	F	N/A
CONSISTANT WITH PLAN REVIEW	[]	[]	[]
 CONFIGURATION (FDC location) 	[]	[]	[]
 VAULT OS&Y VALVE SUPERVISED 	[]	[]	[]
SEALED / NO WATER	[]	[]	[]
SPRINKLER SYSTEM	Р	F	N/A
EXTERIOR AUDIBLE / VISUAL DEVICE	[]	[]	[]
(If system in not monitored, must face the			
Public street side – IFC 903.4.2)			
 STANDPIPES (Stairwells, Buildings 4 stories or taller) 	[]	[]	[]
 STANDPIPE HOOKUPS (21/2" on each valve) 	[]	[]	[]
 STANDPIPE DISTANCE (High Rise Packs 150') 	[]	[]	[]



WEST LAFAYETTE FIRE DEPARTMENT

300 NORTH ST• WEST LAFAYETTE, INDIANA 47906

MAIN PHONE: 765-775-5175

POST INDICATOR VALVE	Р	F	N/A
 HEIGHT REQUIREMENT (36" from grade) 	[]	[]	[]
 MINIMUM OF 40' FROM BUILDING 	[]	[]	[]
 VEHICLE IMPACT PROTECTION 	[]	[]	[]
 SUPERVISED PROPERLY (>20 heads = electronic supervision) 	[]	[]	[]
FIRE LANE	Р	F	N/A
 CONSISTENT WITH PLAN REVIEW 	[]	[]	[]
 IDENTIFIED PROPERLY (Signs & Paint) 	[]	[]	[]
PREMISE IDENTIFICATION	Р	F	N/A
 PROPER SIZE NUMBERS (4") 	[]	[]	[]
 PROPER LOCATION (Street Side) 	[]	[]	[]
 REAR DOOR(s) IDENTIFIED 	[]	[]	[]
FIRE DEPARTMENT ACCESS	Р	F	N/A
 CONSISTENT WITH PLAN REVIEW 	[]	[]	[]
 KNOX BOX (Proper Location) 	[]	[]	[]
 PROPER KEYS (Master / Pull Stations / FAAP) 	[]	[]	[]
 ACCESS ISSUES (Gates, ETC.) 	[]	[]	[]
 VERTICAL HEIGHT (Signage)(Min. 13'5") 	[]	[]	[]
 FIRE LANE (Access of Min. 14' Width & Marked) 	[]	[]	[]
 DRIVE & PARKING LOT LANES, (Min. 24' Width, Dbl. 1 	Lanes) []	[]	[]
 PARKING LOT LANE, (Min. 16' Width, Single One Way 	y Lane)[]	[]	[]
• CORNERS IN LOTS, (Large Radius for Aerial Truck)	[]	[]	[]
UTILITIES	Р	F	N/A
 GAS METERS PROTECTED (Vehicle Impact) 	[]	[]	[]
 GAS METERS IDENTIFIED (Multiple) 	[]	[]	[]
 GAS LINES / METERS SECURED 	[]	[]	[]
 ELECTRICAL EQUIP. PROTECTED (NFPA 100.26) 	[]	[]	[]
 ELECTRICAL METERS/DISCONNECTS IDENTIFIED (Multiple, NFPA 70-110.22) 	[]	[]	[]
ELECTRICAL DISCONNECTS SHALL BE GROUPED (Six Maximum, NEC 230.72)	[]	[]	[]



Office: Mike Francis, Inspector

Office: Tony Schutter Deputy Fire Chief

WEST LAFAYETTE FIRE DEPARTMENT

300 NORTH ST• WEST LAFAYETTE, INDIANA 47906

MAIN PHONE: 765-775-5175

FIRE EX	KTINGUISHERS (NFPA 10 / IFC 9)	Р	F	N/A
•	PROPER TYPE (2A, 4A)	[]	[]	[]
•	TRAVEL DISTANCE *(75')	[]	[]	[]
•	MAXIMUM FLOOR AREA PER EXTINGUISHER (11,250SF)	[]	[]	[]
•	MOUNTED/UNOBSTRUCTED/ACCESSIBLE	[]	[]	[]
•	CLASS K WITHIN 30' COOKING EQUIPMENT	[]	[]	[]
•	40 BC (For Elevator Equipment Room)	[]	[]	[]
<u>PARKII</u>	NG GARAGES	Р	F	N/A
•	3-STORIES OR TALLER, STANDPIPES IN STAIRWELLS	[]	[]	[]
•	INSIDE CLEARENCE (90", MIN. IS 84" & Marked)	[]	[]	[]
•	SPRINKLER & VENTILATION SYSTEM (underground garage)	[]	[]	[]
EXTER	IOR OPENINGS (IBC 903.2)	Р	F	N/A
•	(20 SF every 50 Linear Feet = 1 side 75 ft. = 2 sides	[]	[]	[]
>	Must meet or exceed NFPA requirements			
>	This may not be an all-inclusive list required by the West L request more information prior to final inspection	afayett	e Fire D	ept. WLFD may
*Sprini	kler exception			
Contac	et Information:			
West L	afayette Fire Dept.			

765-775-5178

765-775-5186



WEST LAFAYETTE FIRE DEPARTMENT

300 NORTH ST• WEST LAFAYETTE, INDIANA 47906

MAIN PHONE: 765-775-5175